AMENDMENTS TO THE CLAIMS:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

- 1. (Currently Amended) A method for constructing a high rise building having a core and a residence space around the core, the method comprising the steps of:
 - (a) installing a steel-frame pillar on a shaft portion of the core;
 - (b) connecting a girder to the steel-frame pillar, the girder includes an anchor-connecting member to which a steel-frame beam is connected, a portion of the anchor-connecting member being buried in a core wall;
 - (c) assembling the steel-frame beam on the anchor-connecting member;
- (d) arranging <u>a reinforcing bar bars</u> in a deck plate or a slab type mold installed on the steel-frame beam, and <u>mounting a reinforcing bar on a wall of in</u> the core-wall; and
- (e) applying a slab concrete for a slab and concrete for the wall of the a-core concrete simultaneously or in this order.
- 2. (Previously Presented) The method of claim 1, wherein plural sub-connecting members for supporting the deck plate or the slab type mold are installed on the girder installed

between the steel-frame pillars, the sub-connecting members including a connecting member coupled to the girder and a supporting member coupled to one end of the connecting member.

- 3. (Previously Presented) The method of claim 1, wherein the anchor-connecting member comprises a connecting member connected to the girder by welding or bolts, an anchor plate connected to the connecting member by welding or bolts, a gusset plate welded on the anchor plate, and a stud or shear connector extended from the anchor plate to the concrete wall and buried in the concrete.
- 4. (Previously Presented) The method of claim 1, wherein the step (c) further comprises the steps of forming a slot hole on the anchor-connecting member and coupling a high tensioned bolt in the slot hole to be assembled on the steel-frame beam.